



Declaration of Performance
N° 270-PW4722-1

1. Wood floor 10mm with 0.6mm veneer toplayer on grooved HDF layer to be installed floating or glued down
2. Indoor use
3. Berry Wood – 1790 route de Paris – F-03360 MEAULNE-VITRAY
4. System of assessment and verification of constancy of performance: 3
5. Standard EN 14342: 2013

EUROFINS
Smedeskovvej 38, DK-8464 Galten

- E1 -COV Reports
392-2022-00489301_P_EN
392-2022-00458901_A_EN

CENTEXBEL
Technologiepark 70 • BE-9052 Zwijnaarde

- Fire report
22.06578.00

6. Declared performances

Essential Characteristics	Performances	Reference	Harmonized Standard Specification
Fire reaction linked to : - Conditions of use	C _{fi} -s1 floating or glued down	Centexbel	22.06578.00
Formaldehyde Emissions	E1	Eurofins	392-2022- 00489301_P_EN
Slip resistance	NPD		EN 14342: 2013 392-2022- 00458901_A_EN
PCP Content	<5ppm		
Other dangerous substances emission: - VOC (regulation n°2011-321) - Emission CMR 1 and 2 (arrêté n° DEVP0910046A)	A+ <1µg/m ³	Eurofins	
Thermal conductivity	0,190 (W/K.m)		
Biological Durability	Classe 1		

The performance of the product identified above is in conformity with the declared performances.
According to the regulation (EU) n°305 / 2011, the present declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and behalf of the manufacturer or authorized representative by:
Mr. Valéry MALAVIELLE –Quality/Environment Manager
MEAULNE-VITRAY, May the 28th of 2024