



Declaration of Performance
N° 270-PWDH24-1

1. Wood floor 9.5mm thickness with 0.6mm veneer toplayer on grooved HDF layer to be installed floating or glued down
2. Indoor use
3. Serial N° under each plank with format: DD/MM/YY XXXXXX
4. Berry Wood – 1790 route de Paris – F-03360 MEAULNE-VITRAY
5. System of assessment and verification of constancy of performance: 3
6. Standard EN 14342: 2013

EUROFINS
Smedeskovvej 38, DK-8464 Galten

- E1 -COV Reports
392-2024-00245002_P1_EN
392-2024-00245001_A_EN

CENTEXBEL
Technologiepark 70 • BE-9052 Zwijnaarde

- Fire report
24.02775.01

6. Declared performances

Essential Characteristics	Performances	Reference	Harmonized Standard Specification
Fire reaction linked to : - Conditions of use	C _{fl} -s1 floating or glued down	Centexbel	24.02775.01
Formaldehyde Emissions	E1	Eurofins	392-2024-00245002_P1_EN
Slip resistance	NPD		392-2024-00245001_A_EN
PCP Content	<5ppm		
Other dangerous substances emission: - VOC (regulation n°2011-321) - Emission CMR 1 and 2 (arrêté n° DEVP0910046A)	A <1µg/m³	Eurofins	
Thermal conductivity	0,173 (W/K.m)		
Biological Durability	Classe 1		

The performance of the product identified above is in conformity with the declared performances.
According to the regulation (EU) n°305 / 2011, the present declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and behalf of the manufacturer or authorized representative by:
Mr. Valéry MALAVIELLE –Quality/Environment Manager
MEAULNE-VITRAY, September the 17th of 2024